

SIMONSWERK
TECTUS®

TE 210 3D

for unrebated and rebated, flush-faced quality doors

Hinge **up to 40 kg**

Technical Data

Load capacity	40,0 kg
Length (leaf/frame)	140,0/140,0 mm
Width (leaf/frame)	18,0/21,0 mm
Diameter of cutter	16,0 mm

Descriptive text

SIMONSWERK hinge TECTUS TE 210 3D. Completely concealed for unrebated and rebated, flush-faced quality doors with timber, steel and aluminium frames. CE certified, load capacity 40 kg, opening angle up to 180°, overall length 140 mm, right hand and left hand applicable, maintenance-free slide bearings, three-dimensionally adjustable: Side +/- 3 mm, height +/- 2,5 mm, depth +/- 1,5 mm. Finish...

Combination

Fixing	Block frame	Direct screwing
	Casing frame	TE 210 3D FZ/1
	Steel frame	TE 210 3D SZ
	Aluminium frame	according to specifications of the frame manufacturer

See pages 10 - 11

To be fitted with

Jig	Universal milling frame Drilling jig TE 210 3D
Template	Frame side: No. 5 250663 6 Door side: No. 5 250664 6

Finishes

polished brassed, polished nickelled, F1-coloured, F2-coloured, stainless steel look, powder-coated

Note

Reduced risk of injury due to a very small gap between door leaf and frame.

Quality Marks

