



TE 310 3D

for unrebated premium choice doors

Hinge **up to 60 kg**

Technical Data

Load capacity	60,0 kg
Length (leaf/frame)	140,0/141,0 mm
Width (leaf/frame)	27,5/29,0 mm
Diameter of cutter	24,0 mm

Descriptive text

SIMONSWERK hinge TECTUS TE 310 3D. Completely concealed for unrebated doors with timber, steel and aluminium frames. CE certified, load capacity 60 kg, opening angle up to 180°, overall length 140/141 mm, right hand and left hand applicable, maintenance-free slide bearings, three-dimensionally adjustable: Side +/- 3 mm, height +/- 3 mm, depth +/- 1 mm. Finish...

Combination

Fixing	Block frame	Direct screwing
	Casing frame	TE 310 3D FZ/1
	Steel frame	TE 310 3D SZ
	Aluminium frame	according to specifications of the frame manufacturer

See pages 10 - 11

To be fitted with

Jig	Universal milling frame Drilling jig TE 310 3D
Template	Frame side: No. 5 250371 6 Door side: No. 5 250370 6

Finishes

polished brass, polished nickelled, F1-coloured, F2-coloured, stainless steel look, powder-coated

Note

Reduced risk of injury due to a very small gap between door leaf and frame.

Quality Marks

